

## AREXX TEMPLOGGER SENSOREN DATA

### **TL-3TSN**

#### ***Standard Sensor***

**Transmitting Range;** 50 meter (100 meter Free field)  
**Measurement range;** -30 bis +80 Degrees Celsius,  $\pm 0,5^\circ$  bis  $1^\circ$ .  
**Size (WxDxH in mm);** 58x21x65

### **TSN-33MN**

#### ***MINI Sensor, waterproof***

**Transmitting range;** 25 meter (50 meter Freefield)  
**Measurement range;** -30 to +80 Degrees Celsius,  $\pm 0,5^\circ$  to  $1^\circ$ .  
**Size ( $\emptyset$ xH in mm);** 33x11

### **TSN-EXT44**

#### ***Sensor with external temperature probe***

**Transmitting range;** 90 meter (180 meter Freefield)  
**Measurement range;** -30 to +80 Degrees Celsius,  $\pm 0,5^\circ$  to  $1^\circ$ .  
**Size (WxDxH in mm);** 58x21x65  
**Probe cable length;** 75 cm

### **TSN-50E**

#### ***Sensor bigger range***

**Transmitting range;** 90 meter (180 meter Freefield)  
**Measurement range;** -30 to +80 Degrees Celsius,  $\pm 0,5^\circ$  bis  $1^\circ$ .  
**Size (WxDxH in mm);** 58x21x65

### **TSN-TH70E**

#### ***Sensor Temperature and Humidity.***

**Transmitting range;** 90 meter (180 meter Freefield)  
**Measurement range;** -40 to +120 Degrees Celsius,  $\pm 0,5^\circ$ .  
Relative Humidity 0 to 100% RH,  $\pm 4.5$  % RH  
**Size (WxDxH in mm);** 58x21x65

### **TSN-CO<sub>2</sub> ind**

#### ***Sensor CO<sub>2</sub> Indicator***

**Transmitting range;** 50 meter (100 meter Freefield)  
**Measurement range;** 400 ppm to 90% CO<sub>2</sub>,  $\pm 10$  %  
**Operating conditions;** 10 - 30 Degrees Celsius and 15- to 80% RH Humidity  
**Size (WxDxH in mm);** 58x21x65