

AZ733

DPDT MINIATURE POWER RELAY

FEATURES

- Dielectric strength 5000 Vrms
- Low cost
- Epoxy sealed version available
- 10 Amp switching — double pole contacts
- Isolation spacing greater than 8mm
- UL, CUR file E43203
- TÜV file R9659062



CONTACTS

Arrangement	DPST (2 Form A) DPDT (2 Form C)
Ratings	Resistive load: Max. switched power: 300 W or 2500 VA Max. switched current: 10 A Max. switched voltage: 150 VDC* or 380 VAC * Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
Rated Load UL, CUR	10 A at 250 VAC general use, 100k cycles 10 A at 30 VDC N.O. resistive, 100K cycles 10 A at 30 VDC N.C. resistive, 50K cycles 1/4 HP at 240 VAC 1/8 HP at 120 VAC
TÜV	TV-3 at 125 VAC (2 Form A) 5 A at 30 VDC, 250 VAC resistive, 100k cycles
Material	Silver cadmium oxide
Resistance	< 50 milliohms initially (24 V, 1 A voltage drop method)

COIL

Power At Pickup Voltage (typical)	257 mW
Max. Continuous Dissipation	1.9 W at 20°C (68°F) ambient
Temperature Rise	34°C (61°F) at nominal coil voltage
Temperature	Max. 130°C (266°F)

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁷ 1 x 10 ⁵ at 10 A 250 VAC Res.
Operate Time (typical)	8 ms at nominal coil voltage
Release Time (typical)	5 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	5000 Vrms contact to coil 1000 Vrms between open contacts 3000 Vrms between contact sets
Insulation Resistance	1000 megohms min. at 20°C, 500 VDC, 50% RH
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	-40°C (-40°F) to 85°C (185°F) -40°C (-40°F) to 105°C (266°F)
Vibration	0.062" (1.5 mm) DA at 10–55 Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	18 grams
Packing unit in pcs	50 per plastic tray / 500 per carton box

ZETTLER electronics GmbH

Junkersstrasse 3, D-82178 Puchheim, Germany

Tel. +49 89 800 97 0
Fax +49 89 800 97 200

office@ZETTLERelectronics.com
www.ZETTLERelectronics.com

AZ733

RELAY ORDERING DATA

COIL SPECIFICATIONS				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance Ohm	Form A (DPST)	Form C (DPDT)
3	2.1	5.7	17 ±10%	AZ733-2A-3D	AZ733-2C-3D
5	3.5	9.4	47 ±10%	AZ733-2A-5D	AZ733-2C-5D
6	4.2	11.4	68 ±10%	AZ733-2A-6D	AZ733-2C-6D
9	6.3	17.4	160 ±10%	AZ733-2A-9D	AZ733-2C-9D
12	8.4	22.8	275 ±10%	AZ733-2A-12D	AZ733-2C-12D
18	12.6	27.9	650 ±10%	AZ733-2A-18D	AZ733-2C-18D
24	16.8	45.7	1,100 ±15%	AZ733-2A-24D	AZ733-2C-24D
48	33.6	89.0	4,170 ±15%	AZ733-2A-48D	AZ733-2C-48D
60	42.0	115.3	7,000 ±15%	AZ733-2A-60D	AZ733-2C-60D
110 **	79.3	170.5	22,900 ±15%	AZ733-2A-110D	AZ733-2C-110D

* Add suffix "E" for epoxy sealed version.

** 110 VDC coil not TÜV approved.

MECHANICAL DATA

Terminal No.	Dimensions Tol.: ± 0.005 (0.13)
1,2,4,5,7,8	0.018 (0.457) x 0.038 (0.965)
3,6	0.011 (0.279) x 0.038 (0.965)

PC BOARD LAYOUT

(Form C only)

Viewed toward terminals

WIRING DIAGRAM

Form A

Form C

Viewed toward terminals

Dimensions in inches with metric equivalents in parentheses. Tolerance: ± .010"