


THERMO-HYGRO MONITOR

Instruction Manual



INTRODUCTION:

Congratulations on purchasing this stylish thermo-hygro monitor which displays indoor temperature and indoor humidity readings. This tiny monitor is ideal for using at home and in office.



LCD SCREEN

The LCD is divided into 2 sections, displaying indoor temperature and indoor humidity



FEATURES:

- Indoor temperature displayed in degree Celsius (°C)
- Indoor relative humidity displayed in %RH
- Wall mounting or table standing (foldout table stand)

SETTING UP:

The thermo-hygro monitor uses 2 x AAA, IEC LR3, 1.5V batteries. To install and replace the batteries, please follow the steps below:

1. Insert finger or other solid object in the space at the bottom center of the battery compartment and lift up to remove the cover.
2. Insert batteries observing the correct polarity (see marking).
3. Replace compartment cover.

Once the batteries are in place, all segments of the LCD will light up briefly. Then the indoor temperature and humidity readings will be displayed. If the indoor temperature and humidity are not displayed after a few seconds, remove the batteries and wait for at least 30 seconds before reinserting them.


BATTERY CHANGE

It is recommended to replace the batteries on an annual basis to ensure optimum accuracy of these units.



Please participate in the preservation of the environment. Return used batteries to an authorized depot.

POSITIONING THE THERMO-HYGRO MONITOR:



The thermo-hygro monitor comes complete with a stand, which gives the option of table standing or wall mounting. To wall mount:

1. Fix a screw into the desired wall, leaving the head extended out by about 5mm.
2. Using the thermo-hygro monitor's hanging hole, carefully hang it onto the screw.

Note: Always ensure that the unit locks onto the screw head before releasing.

CARE AND MAINTENANCE:

- Avoid placing the unit in areas prone to vibration and shock as these may cause damage.
- Avoid areas where the unit can be exposed to sudden changes in temperature, i.e. direct sunlight, extreme cold and wet/moist conditions as these will lead to rapid changes in temperature which reduces the accuracy of readings.
- When cleaning the LCD and casing, use a soft damp cloth only. Do not use solvents or scouring agents.
- Do not submerge the unit into water.
- Immediately remove all low powered batteries to avoid leakage and damage.
- Replace only with new batteries of the recommended size.
- Do not make any repairs to the unit. Please return it to the original point of purchase for repair by a qualified engineer. Opening and tampering with the unit may invalidate its guarantee.

SPECIFICATIONS:

Indoor temperature measuring range : - 9.9 to +69.9°C with 0.1°C resolution ("OF.L°C" displayed if outside this range)

Indoor relative humidity measuring range : 1% to 99% with 1% resolution (" - %" displayed if outside this range)"

Indoor temperature and humidity checking intervals : every 10 seconds

Power source : 2 x AAA, IEC LR3, 1.5V batteries

Battery life : Approximately 12 months (Alkaline batteries recommended)

Dimensions (L x W x H) : 117.9 x 17 x 108.2 mm

LIABILITY DISCLAIMER:

- The manufacturer and supplier cannot accept any responsibility for any incorrect readings and any consequences that occur should an inaccurate reading take place.
- This product is designed for use in the home only as indication of the temperature.
- This product is not to be used for medical purposes or for public information.
- The specifications of this product may change without prior notice.
- This product is not a toy. Keep out of the reach of children.
- No part of this manual may be reproduced without written authorization of the manufacturer.